

Fire Extinguisher Cabinets

Fire Extinguishers installed in aggressive environments such as where there is a high level of moisture, dust laden, corrosive areas or direct UV exposure should be pressure tested and refilled every **THREE** years instead of every five years according to the requirements of Australian Standard AS 1851. Save on your maintenance costs by installing the equipment in a cabinet.



'DOME LID' FIRE EXTINGUISHER CABINETS:

DOME LID CABINETS ARE PARTICULARLY IDEAL FOR INSTALLATION IN MOISTURE AND DUST LADEN AREAS AND ALSO HIGH TRAFFIC AREAS SUCH AS RAIL OR BUS STATIONS.

- UV RESISTANT MATERIAL
- NO SHARP EDGES.
- QUICK ACCESS
- AVAILABLE IN A RANGE OF SIZES TO SUIT ANY EXTINGUISHER

PRODUCT CODES:

- PDL – 3:** Suits 2.5kg to 4.5kg Extinguishers
PDL – 1: Suits 6.0kg to 9.0kg Extinguishers
PDL – 2: Suits 5.0kg CO2 Extinguishers

'METAL LOCKING' FIRE EXTINGUISHER CABINETS:

METAL LOCKING CABINETS ARE IDEAL FOR INSTALLATION IN AREAS WHERE THEFT OR VANDALISM IS A RISK.

- EASY BREAK PANEL ACCESS IN AN EMERGENCY
- FIRE SERVICE '003' KEY LOCK.
- POLYESTER POWDER COATED FOR UV RESISTANCE
- ECONOMICAL EQUIPMENT 'SECURITY'

PRODUCT CODES

- ECM – S:** Suits 1.0kg to 2.0kg Extinguishers
ECM – M: Suits 2.5kg to 4.5kg Extinguishers
ECM – L: Suits 4.5kg to 9.0kg Extinguishers

