

Wet Chemical Type



EXTINGUISHER TYPE: Wet Chemical

IDENTIFICATION:

Pre 1998 - Oatmeal
 Post 1998 - Red with upper level **Oatmeal** Band

ADVANTAGES:

Specifically engineered for restaurant & cafe kitchens fitted with deep fat fryers. The most effective extinguishant for use on vegetable based cooking oil fires.

DISADVANTAGES:

Depending upon application, specialised training is advisable. Not suitable for electrically energised fire risks.

SERVICING:

Inspection and maintenance is to be performed at regular six monthly intervals as required by Australian Standard AS 1851 by Protector Fire Services or an authorised distributor.

SPECIFICATION DATA:

MODEL	FE7WC	
FILL CAPACITY (LITRE)	7.0	
VALVE	CHROME PLATED BRASS WITH CONTROLLABLE DISCHARGE & PRESSURE INDICATOR	
CYLINDER SPECIFICATION	304 GRADE STAINLESS STEEL – 1.0mm	
BODY DIAMETER (mm)	180	
OVERALL HEIGHT (mm)	630	
APPROX. FULL MASS (kg)	12.0	
WORKING PRESSURE	700 kPa @ 23 +/- 2°c	
CYLINDER TEST PRESSURE (MPa)	2.0	
APPROX. DISCHARGE TIME (sec)		
FIRE RATING – ‘STILL AIR’		
DISCHARGE ASSEMBLY TYPE	DISCHARGE HOSE & JET NOZZLE ASSY.	DISCHARGE HOSE & ASPIRATING NOZZLE
PAINT FINISH	SIGNAL RED (R13) POLYESTER POWDER COATING	
MOUNTING	METAL WALL BRACKET	
DESIGN and MANUFACTURE	AS/NZS 1841	

SUITABILITY GUIDE	CLASS A PAPER ETC	CLASS B FLAM. LIQUID	CLASS C FLAM GAS	CLASS D COMB METAL	CLASS E ELECTRICAL	CLASS F COOKING OIL
	LIMITED	LIMITED	NO	NO	NO	YES